

New

Programmable Electric Under-Floor Heating Control



- **Programmable digital thermostat complete with floor probe**

These ultra-compact thermostats provide precise control of either ambient temperature with a floor temperature limit or floor temperature control.

Features

Microprocessor-optimized PIA

Heating cycles: 15 min.

Accuracy: $\pm 0.5^{\circ}\text{C} / 0.9^{\circ}\text{F}$

7-day, 4 time periods/day, 2 temp. settings

Early Start function

24-hour clock / $^{\circ}\text{C}$ or $^{\circ}\text{F}$

Dimensions 82 x 78 x 25 mm

Floor sensor include

Wall plate for NZ Flush box, AC130-12-P10

TH132 Under Floor Heating Thermostat				
<i>Model Number</i>	<i>Switching Application</i>	<i>Electrical Rating</i>	<i>Range</i>	<i>Features</i>
TH132-AF-230	Heating only Air control with floor limit	15A Resistive 230 VAC 3.45 kW	5 to 30°C	3 m floor probe Fits Euro flush box or use wall plate
TH132-F-230	Heating only Floor control	15A Resistive 230 VAC 3.45 kW	5 to 30°C	3 m floor probe Fits Euro flush box or use wall plate



- **Electronic dial thermostat complete with floor probe**

These ultra-compact thermostats provide precise control of either ambient temperature with a floor temperature limit or floor temperature control.

Features

Microprocessor-optimized PIA

Heating cycles: 15 min.

Accuracy: $\pm 0.5^{\circ}\text{C} / 0.9^{\circ}\text{F}$

Dimensions 82 x 78 x 25 mm

Floor sensor included

Installer set point limits

Wall plate for NZ Flush box, AC130-12-P10

TH131 Under Floor Heating Thermostat				
<i>Model Number</i>	<i>Switching Application</i>	<i>Electrical Rating</i>	<i>Range</i>	<i>Features</i>
TH131-AF-230	Heating only Air control with floor limit	15A Resistive 230 VAC 3.45 kW	15 to 35°C Min position is 7°C	3 m floor probe Fits Euro flush box or use wall plate
TH131-F-230	Heating only Floor control	15A Resistive 230 VAC 3.45 kW	15 to 35°C Min position is 7°C	3 m floor probe Fits Euro flush box or use wall plate